

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



10/525628



(43) International Publication Date
11 March 2004 (11.03.2004)


PCT

(10) International Publication Number
WO 2004/021080 A1

- (51) International Patent Classification⁷: G03C 1/76, B41M 5/40, G03F 7/095, B41N 1/00
- (21) International Application Number: PCT/BR2003/000119
- (22) International Filing Date: 22 August 2003 (22.08.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PI02034280 29 August 2002 (29.08.2002) BR
C102034280 17 December 2002 (17.12.2002) BR
- (71) Applicant and
(72) Inventor: DANTAS, Eudes [BR/BR]; Rua Evaristo da Veiga, 41 / Apto 104 - Centro, 20031-040 Rio de Janeiro - RJ (BR).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Declaration under Rule 4.17:
— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: STEREOFLEXOGRAPHY



(57) Abstract: Improvement to the photopolymers catalysis in printing plates for the flexographic and of stamp sectors (fig.1), by exposing the photopolymer plate (1), only, by the bottom face (2), to two different and simultaneous levels of radiation; a lower, to catalyze the base of the relief (8) and a maximum, to catalyze the printing relief (10), emitted by radiation device (5, 6), polarized by filter (7), which uses a negative film whose black area is replaced by halftone (3), thereby originating the low radiation level, and keeping its transparent area (4), thereby originating the maximum radiation level, thickening the base of the dot (9) and sharpening the top of the dot (10), thereby eliminating the 'dot droop' and the 'dot gain', respectively; or which uses optic semiconductors, which digitally modulate the radiation in a fixed way (fig.2) for the stamp sector, with DMD or LCD (1), and in a mobile way (fig.3), with DMD (1), for the flexographic sector.

WO 2004/021080 A1